

HYBRID INVERTER

PRODUCT FEATURES

- ◇ 100% Pure Sine wave Inverter
- ◇ Inverter with Battery equalization
- ◇ Upgraded Generation Smart and intelligent solar Inverter
- ◇ MPPT Based solar charge controller
- ◇ Output power factor 1
- ◇ Adaptable to main voltage / Generator Power
- ◇ Compatible with SNMP box / Wi-Fi Box
- ◇ New smart LCD display
- ◇ Conformal Coating to Prevent from Dust and Humidity
- ◇ Configurable AC/Solar input Priority Via LCD Setting
- ◇ Overload and Short Circuit Protection

**LEADING
BRAND**

**UPGRADED
VERSION**



MODEL

REVO
VM 3200-24

Rated Power

3200VA/3000W

INPUT

Voltage

230 VAC

Selectable Voltage Range

170-280 VAC (For Personal Computers) : 90-280 VAC (For Home Appliances)

Frequency Range

50 Hz/60 Hz (Auto sensing)

OUTPUT

AC Voltage Regulation (Batt. Mode)

230VAC \pm 5%

Surge Power

6000VA

Efficiency (Peak)

90% ~ 93%

Transfer Time

10 ms (For Personal Computers) : 20 ms (For Home Appliances)

Waveform

Pure sine wave

BATTERY

Battery Voltage

24 VDC

Floating Charge Voltage

27 VDC

Overcharge Protection

33 VDC

SOLAR CHARGER & AC CHARGER

Solar Charger type

MPPT

Maximum PV Array Open Circuit Voltage

100 VDC

Maximum PV Array Power

3000 W

MPP Range @ Operating Voltage

30 ~ 80 VDC

Maximum Solar Charge Current

65 A

Maximum AC Charge Current

60 A

Maximum Charge Current

125 A

ENVIRONMENT

Humidity

5% to 95% Relative Humidity (Non-condensing)

Operating Temperature

-10°C to 50°C

Storage Temperature

-15°C to 60°C

Design & Engineering in Taiwan

**PAY LESS
BILL**

PRODUCE MAXIMUM ENERGY
FROM THE SUN

Ready to Reduce Your Electricity Bills with New Revo Series

2 | Year Warranty
Terms & condition apply

